

XECHO - i1802

Eco Solvent Printer (With 2 Heads)


F Sign & Display



Eco Solvent / Sublimation



Two I3200 Heads



* 1.8m Dual I3200 Print Heads Speed

360x1800dpi - 3pass	55 m ² /h
720x1200dpi - 4pass	40 m ² /h
720x1800dpi - 6pass	27 m ² /h

Our range of wide format inkjet printers matches our knack for engineering and quality with your desire for impeccable performance and careless production. You can produce roll-to-roll indoor prints and long term outdoor signs. Wide applications in light box posters, customized car stickers, background wall cloth, label printing, advertising sign, subway advertising, shopping mall advertising signs etc.




● Technical Specifications


Model	GD1802-TX(I3200)	GD3202-TX(I3200)
Print Head	Dual I3200 Print Heads	Dual I3200 Print Heads
Printing Technology	Piezoelectric Inkjet	
Acceptable Media	Width 71.6 in.(1820 mm) Thickness Maximum 39 mil(1 mm) Weight 132.2 lb.(60 kg)	128 in.(3250 mm) Maximum 39 mil(1 mm) 176 lb.(80 kg)
Printing Width	70.8 in.(1800 mm)	126 in.(3200 mm)
Ink Cartridges	Type Dye Sublimation Ink Capacity 4*4 CISS (220ml ink cartridge with 1.5L ink tank) 6*6 CISS (6 color), 8*8 CISS (8 color) optional Color 4 colors (Cyan, Magenta, Yellow, Black) 6 colors, 8 colors optional	
Printing Resolution	Maximum 1440 dpi	Maximum 1440 dpi
Printing Speed	4pass(720x720dpi): 333 sqft (31 sqm/h) 6pass(720x1080dpi): 225 sqft (21 sqm/h) 8pass(720x1440dpi): 182 sqft (17 sqm/h)	3pass(360x1800dpi): 590 sqft (55 sqm/h) 4pass(720x1200dpi): 429 sqft (40 sqm/h) 6pass(720x1800dpi): 290 sqft (27 sqm/h)
Media Heating System	Integrated post heater & Infrared Dryer & Fan system	
Interface	USB 2.0	USB 2.0
Power Supply	AC 220V ± 10%, 50/60 HZ	USB 3.0/LAN
Dimensions(with stand)	128(W)x26(D)x53(H) in. (3190(W)x650(D)x1360(H) mm)	180(W)x38(D)x62(H) in. (4580(W)x970(D)x1580(H) mm)
Weight(with stand)	882 lb. (400 kg)	2204 lb. (1000 kg)
Package Dimensions	Entirety Packing : 3360(W)x950(D)x1560(H) mm Split Packing : 3350(W)x820(D)x1030(H) mm	195(W)x44(D)x71(H) in. (4940(W)x1130(D)x1810(H) mm)
Package Weight	Entirety Packing : 1102.5 lb. (500 kg) Split Packing : 1068.4 lb. (480 kg)	2535 lb. (1150 kg)
Environment	Power on Temperature: 59 ℉ to 90 ℉ [15 ℃ to 32 ℃] (68 ℉ [20 ℃] / Humidity: 35 to 80% (no condensation) Power off Temperature: 41 ℉ to 104 ℉ [5 ℃ to 40 ℃] / Humidity: 20 to 80% (no condensation)	
Accessories	USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.	




THK high-precision mute rail.




High-precision and high-stability tensioning pulley system.




The automatic cleaning assembly adds a single-way valve to increase the stability of the ink supply.



Automatic moisturizing cleaning assembly ensures the stability of head cleaning and improves working stability.




New pinch roller structure of three in group brings more stable feeding precision.



High quality DC servo motor with good stability and long life.




Infrared heater and cooling fan.




External power supply, intelligent rolling system

Both the sublimation and direct-to-textile printers are examples of our expertise and engineering: top performance, reliable and precise. With Grando series printer, you can maximize production while controlling quality and minimizing costs for beautiful soft signage, apparel and interior decor items that will set your business apart from the competition. Wide applications in clothing, home decoration fabrics, sampling, shirt, canvas bags, bolster, scooter, flags, textile gadgets etc.




● Technical Specifications

Model	GD1802-TX(I3200)		GD3202-TX(I3200)	
Print Head	Dual I3200 Print Heads		Dual I3200 Print Heads	
Printing Technology	Piezoelectric Inkjet			
Acceptable Media	Width	71.6 in.(1820 mm)	128 in.(3250 mm)	
	Thickness	Maximum 39 mil(1 mm)	Maximum 39 mil(1 mm)	
	Weight	132.2 lb.(60 kg)	176 lb.(80 kg)	
Printing Width	70.8 in.(1800 mm)		126 in.(3200 mm)	
Ink Cartridges	Type	Dye Sublimation Ink		
	Capacity	4*4 CISS (220ml ink cartridge with 1.5L ink tank) 6*6 CISS (6 color), 8*8 CISS (8 color) optional		
	Color	4 colors (Cyan, Magenta, Yellow, Black) 6 colors, 8 colors optional		
Printing Resolution	Maximum 1440 dpi	Maximum 2400 dpi	Maximum 1440 dpi	Maximum 2400 dpi
Printing Speed	4pass(720x720dpi) 333 sqft (31 sqm/h)	3pass(360x1800dpi) 560 sqft (55 sqm/h)	4pass(720x720dpi) 354 sqft (33 sqm/h)	3pass(360x1800dpi) 667 sqft (62 sqm/h)
	6pass(720x1080dpi) 225 sqft (21 sqm/h)	4pass(720x1200dpi) 429 sqft (40 sqm/h)	6pass(720x1080dpi) 279 sqft (26 sqm/h)	4pass(720x1200dpi) 506 sqft (47 sqm/h)
	8pass(720x1440dpi) 162 sqft (17 sqm/h)	6pass(720x1800dpi) 290 sqft (27 sqm/h)	8pass(720x1440dpi) 193 sqft (18 sqm/h)	6pass(720x1800dpi) 334 sqft (31 sqm/h)
Media Heating System	Integrated post heater & Infrared Dryer & Fan system			
Interface	USB 2.0	USB 3.0/LAN	USB 2.0	USB 3.0/LAN
Power Supply	AC 220V ± 10%, 50/60 HZ			
Dimensions(with stand)	126(W)x26(D)x53(H) in. (3190(W)x650(D)x1360(H) mm)		180(W)x38(D)x62(H) in. (4580(W)x970(D)x1580(H) mm)	
Weight(with stand)	882 lb. (400 kg)		2204 lb. (1000 kg)	
Package Dimensions	Entirety Packing : 3360(W)x950(D)x1560(H) mm		195(W)x44(D)x71(H) in.	
	Split Packing : 3350(W)x820(D)x1030(H) mm		(4940(W)x1130(D)x1810(H) mm)	
Package Weight	Entirety Packing : 1102.5 lb.(500 kg) Split Packing : 1058.4 lb.(480 kg)		2535 lb. (1150 kg)	
Environment	Power on Temperature: 59 ℉ to 90 ℉ [15℃ to 32℃] (68 ℉ [20℃] / Humidity: 35 to 80% (no condensation)			
	Power off Temperature: 41 ℉ to 104 ℉ [5℃ to 40℃] / Humidity: 20 to 80% (no condensation)			
Accessories	USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.			




Three stage heating system including pre-heater, print heater, and rear heater and platform vacuum system with adjustable power.




New pinch roller structure of three in group brings more stable feeding precision.




THK high-precision mute rail.




High quality DC servo motor with good stability and long life.




High-precision and high-stability tensioning pulley system.



The automatic cleaning assembly adds a single-way valve to increase the stability of the ink supply.



Automatic moisturizing cleaning assembly ensures the stability of head cleaning and improves working stability.



External power supply, intelligent rolling system.